



### Area of application

Primer for concrete base



### Description

PROJISO FIXO-B is a vinyl derivative solution with a high molecular weight and a high degree of polymerization. It is a primer for mineral fibres sprayed onto concrete.

### Installation

PROJISO FIXO-B® is installed using a brush, roller or low-pressure sprayer on a clean, intact base. The spray-on coating must be sprayed while the primer is still sticky.

### Environment and safety

Refer to the environmental and safety declaration (FDES) and the safety datasheet (SDS), available upon request. Do not discharge into drains, rivers or soil. Use the garbage bags provided for this purpose.

### Packaging and storage

- Shelf life: maximum 12 months in the original hermetically sealed barrels.
- Storage conditions: store indoors in dry conditions between 5 and 45°C. Avoid frost.
- Packaging: 25 kg PE barrels.
- Palletization: At least 24 barrels per pallet, or 600kg.

### Characteristics

Colour	Colourless
Specific weight	1 ± 0,5 g/cm <sup>3</sup>
pH	5
Dilution	Do not dilute
Consumption	Approximately 100 g/m <sup>2</sup> May depend on the base quality
Application temperature	5 - 45 °C
Film formation time	Around 30 minutes at 20°C / 60% RH
Drying time at 20°C and 60% RH	1 hour (dry to the touch) 3 – 4 days to fully dry
Brookfield viscosity at 25°C	280-380 cps
Number of coats	NA
Setting method	Air drying
Reaction to fire	NA
VOC classification	A+

The information given in this technical document is based on real tests and is presumed to be specific to the product. Results are not implicitly guaranteed, as the use conditions are outside our control.