



Area of application

Primer for metal base



Description

PROJISO FIXO-M® is a watery dispersion of a styrene butadiene copolymer.

It is a synthetic adhesive designed to be used to fasten the sprayed-on mineral fibre to the metal base.

Installation

PROJISO FIXO-M® is installed using a brush, roller or low-pressure sprayer on a clean, intact base. The spray-on coating must be sprayed while the primer is still sticky.

Environment and safety

Refer to the environmental and safety declaration (FDES) and the safety datasheet (SDS), available upon request.

Do not discharge into drains, rivers or soil. Use the garbage bags provided for this purpose.

Packaging and storage

- Shelf life: maximum 12 months in the original hermetically sealed barrels.
- Storage conditions: store indoors in dry conditions between 5 and 45°C. Avoid frost.
- Packaging: 25 kg PE barrels.
- Palletization: 24 barrels per pallet, or 600kg.

Characteristics

Colour	Milky white
Specific weight	1,15 ±0,05 g/cm ³
pH	7
Dilution	Do not dilute
Consumption	200 à 250 g/m ²
Application temperature	5 - 45 °C
Film formation time	Around 45 minutes at 20°C / 60% RH
Drying time at 20°C and 60% RH	6 hours (dry to the touch) 3 – 4 days to fully dry
Brookfield viscosity at 25°C	1600 - 2200 cps
Number of coats	NA
Setting method	Air drying
Reaction to fire	NA
VOC classification	A+

The information given in this technical document is based on real tests and is presumed to be specific to the product. Results are not implicitly guaranteed, as the use conditions are outside our control.